

# EMS-D 5025

## Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Motor Tipi / Motor Type	Güç / Power	Güç / Power	m³/h	0	10,8	14,4	18	21,6	25	28,8	32,4	36	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
		HP	kW		lt/s	0	3	4	5	6	7	8	9		10	mm	mm	LA (mm)
5025 / 03	4" 5" 6"	3	2,2	MMS (m)	27	25	23	22	20	19	18	16	15	2 1/2" 3"	125	135	750	24
5025 / 04		4	3		36	32	30	28	27	26	24	22	20				833	27
5025 / 05		5,5	4		45	38	37	36	34	32	30	28	25				916	30
5025 / 09		7,5	5,5		72	62	60	57	54	52	47	43	40				1082	36
5025 / 10		10	7,5		85	77	73	71	68	64	60	55	52				1248	42
5025 / 12		12,5	9,2		100	92	88	85	80	78	72	67	62				1497	51
5025 / 15		15	11		125	115	110	105	100	92	87	78	70				1663	57

### ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

### PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		