

# EMS-D 9180

## Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi/ Pump Type	Motor Tipi/ Motor Type	Güç/ Power	Güç/ Power	m <sup>3</sup> /h	0	102	128	180	189	205	221	240	253	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu/ Pump Length	Pompa Ağırlığı/ Pump Weight
		HP	kW		0	28,3	35,5	50	52,5	56,9	61,4	66,7	70		mm	mm	LA (mm)	Kg
9180 / 01	6" 8"	25	18,5	MMS (m)	34	30	24	21	19	18	17	16	15	6"	225	240	635	56
9180 / 02		50	37		65	50	45	42	40	38	36	32	30				800	80
9180 / 03		70	51		96	86	76	69	61	57	54	48	44				965	102
9180 / 04		90	66		124	114	104	96	84	77	74	66	58				1130	125
9180 / 05		110	81		154	144	128	119	98	94	91	83	73				1295	149

### ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

### PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		