

EMS-N 411

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Güç / Power	Güç / Power	m ³ /h	0	3,6	4,8	6	9	12	15	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
	HP	kW		0	10	1,33	1,66	2,50	3,33	4,16		mm	mm	LA (mm)	Kg
411-07	2	1,5	MMS (m)	44	41	40	38	32	22	8	2"	94	98	425	4,7
411-10	3	2,2		63	59	57	55	46	31	11				805	4,9
411-12	4	3		76	71	69	66	55	37	13				910	5,6
411-14	4	3		88	82	79	77	64	43	15				1016	6,1
411-17	5,5	4		107	100	97	94	78	53	19				1174	7,2
411-19	5,5	4		120	112	108	105	87	59	21				1280	7,9
411-24	7,5	5,5		151	142	137	132	110	75	27				1578	9,6
411-26	7,5	5,5		163	153	148	142	119	80	28				1684	10,3
411-31	7,5	5,5		195	183	177	170	143	96	34				1941	12
411-32	7,5	5,5		201	188	182	175	147	99	35				1994	12,6
411-38	10	7,5		238	223	216	208	174	117	41				2312	14,8
411-44	10	7,5		276	259	251	241	202	136	48				2654	17,2

ÜRÜN ÖZELLİKLERİ

Pompa Gövdesi	Paslanmaz Çelik	AISI 304
Pompa Mili	Paslanmaz Çelik	AISI 420
Difüzör	Plastik	Norly (PPO)
Difüzör Çanağı	Paslanmaz Çelik	AISI 304
Fan	Plastik	Norly (PPO)
Kaplin	Paslanmaz Çelik	AISI 304
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Yatak Takımı	Kauçuk	NBR
Çanak Yatağı	Plastik	Poliüretan
Klepe	Paslanmaz Çelik	AISI 304
Emiş Gövdesi	Paslanmaz Çelik	AISI 304
Çıkış Gövdesi	Paslanmaz Çelik	AISI 304

PRODUCT SPECIFICATIONS

Pump Body	Stainless Steel	AISI 304
Pump Shaft	Stainless Steel	AISI 420
Diffuser	Plastic	Norly (PPO)
Diffuser Ring	Stainless Steel	AISI 304
Impeller	Plastic	Norly (PPO)
Coupling	Stainless Steel	AISI 304
Filter & Cable Guard	Stainless Steel	AISI 304
Bearing Set	Rubber	NBR
Diffuser Bearing	Plastic	Poliüretan
Valve Cap	Stainless Steel	AISI 304
Suction Body	Stainless Steel	AISI 304
Delivery Body	Stainless Steel	AISI 304