

EMS-N 418

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Güç / Power	Güç / Power	m ³ /h	0	6	9	12	15	18	21	24	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
	HP	kW		0	1,66	2,50	3,33	4,16	5	5,83	6,66		mm			
418-06	2	1,5	MMS (m)	33	29	27	23	20	17	11	5	2"	94	98	425	4,7
418-07	3	2,2		38	34	31	27	23	20	13	6				834	5,8
418-08	3	2,2		44	39	36	31	27	23	15	7				905	6,5
418-09	4	3		49	44	40	37	29	25	16	8				979	7,1
418-11	4	3		61	53	50	42	37	31	20	9				1130	8,4
418-12	5,5	4		65	58	53	46	39	34	22	10				1210	9
418-15	5,5	4		83	73	68	58	50	43	28	13				1426	10,7
418-16	7,5	5,5		86	77	71	61	51	45	29	13				1506	11,2
418-20	7,5	5,5		110	97	90	77	67	57	37	17				1796	13,7
418-22	10	7,5		118	106	97	84	71	62	40	18				1998	14,9
418-26	10	7,5		143	125	117	99	86	73	47	19				2295	17,3
418-30	10	7,5		165	145	135	115	100	85	55	21				2587	19,7

ÜRÜN ÖZELLİKLERİ

Pompa Gövdesi	Paslanmaz Çelik	AISI 304
Pompa Mili	Paslanmaz Çelik	AISI 420
Difüzör	Plastik	Norly (PPO)
Difüzör Çanağı	Paslanmaz Çelik	AISI 304
Fan	Plastik	Norly (PPO)
Kaplin	Paslanmaz Çelik	AISI 304
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Yatak Takımı	Kauçuk	NBR
Çanak Yatağı	Plastik	Poliüretan
Klepe	Paslanmaz Çelik	AISI 304
Emiş Gövdesi	Paslanmaz Çelik	AISI 304
Çıkış Gövdesi	Paslanmaz Çelik	AISI 304

PRODUCT SPECIFICATIONS

Pump Body	Stainless Steel	AISI 304
Pump Shaft	Stainless Steel	AISI 420
Diffuser	Plastic	Norly (PPO)
Diffuser Ring	Stainless Steel	AISI 304
Impeller	Plastic	Norly (PPO)
Coupling	Stainless Steel	AISI 304
Filter & Cable Guard	Stainless Steel	AISI 304
Bearing Set	Rubber	NBR
Diffuser Bearing	Plastic	Poliüretan
Valve Cap	Stainless Steel	AISI 304
Suction Body	Stainless Steel	AISI 304
Delivery Body	Stainless Steel	AISI 304